

Borehole

22-10-05

Log Event A

Borehole Information

Farm : <u>BY</u>	Tank : <u>BY-110</u>	Site Number : <u>299-E33-124</u>
N-Coord : <u>45,860</u>	W-Coord : <u>53,531</u>	TOC Elevation : <u>649.59</u>
Water Level, ft :	Date Drilled : <u>8/31/1970</u>	

Casing Record

Type : <u>Steel-welded</u>	Thickness : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>101</u>	

Borehole Notes:

According to the driller's records, this borehole was not perforated or grouted.

Equipment Information

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>03/1995</u>	Calibration Reference : <u>GJPO-HAN-1</u>	Logging Procedure : <u>P-GJPO-1783</u>

Log Run Information

Log Run Number : <u>1</u>	Log Run Date : <u>9/13/1995</u>	Logging Engineer: <u>Mike Widdop</u>
Start Depth, ft.: <u>98.8</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>5.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>

Log Run Number : <u>2</u>	Log Run Date : <u>9/14/1995</u>	Logging Engineer: <u>Widdop/Pearson</u>
Start Depth, ft.: <u>6.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>0.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>



Spectral Gamma-Ray Borehole
Log Data Report

Page 2 of 2

Borehole

22-10-05

Log Event A

Analysis Information

Analyst : S.E. Kos

Data Processing Reference : P-GJPO-1787

Analysis Date : 3/15/1996

Analysis Notes :

This borehole was logged in two log runs. The pre- and post-field verification spectra indicate that the logging system was operating properly during data collection. The energy/channel drift observed during the logging runs did not exceed the search parameters of the processing software, and multiple energy calibrations were not required to process the data.

The casing thickness is 5/16 (0.313) in. The casing correction used to process the data was for 0.330-in. casing; therefore, slight over-estimations of radionuclide concentrations were calculated.

Cs-137 and Co-60 were the only man-made radionuclides detected in this borehole. The presence of Cs-137 was detected from ground surface to a depth of about 20 ft, intermittently from 21 to 30 ft, at a few isolated locations throughout the borehole, and at the bottom of the borehole. The presence of Co-60 was detected from 48 to 77 ft and from 97 to 99 ft (TD).

Details regarding the interpretation of the data for this borehole are presented in the Tank Summary Data Report for tank BY-110.

Log Plot Notes:

Separate log plots show the man-made (e.g., Cs-137) and the naturally occurring radionuclides (K-40, U-238, and Th-232). The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

A combination plot includes both the man-made and natural radionuclides, in addition to the total gamma derived from the spectral data and the Westinghouse Hanford Company (WHC) Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data from WHC with no attempt to adjust the depths to coincide with the SGLS data.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the minimum detection level (MDL). The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.